# LLM4CBI: Taming LLMs to Generate Effective Test Programs for Compiler Bug Isolation

Haoxin Tu, Zhide Zhou, He Jiang\*, Imam Nur Bani Yusuf, Yuxian Li, Lingxiao Jiang

**Abstract**—Compiler bugs pose a significant threat to safety-critical applications, and promptly and effectively isolating these bugs is crucial for assuring the quality of compilers. However, the limited availability of debugging information on reported bugs complicates the compiler bug isolation task. Existing compiler bug isolation approaches typically convert the problem into a test program mutation problem, but they are still limited by ineffective mutation strategies or high human effort requirements. Drawing inspiration from the recent progress of pre-trained Large Language Models (LLMs), such as ChatGPT, in code generation, we propose a new approach named LLM4CBI to tame LLMs to generate effective test programs for compiler bug isolation. However, using LLMs directly for test program mutation may not yield the desired results due to the challenges associated with formulating precise prompts and selecting specialized prompts. To overcome the challenges, three new components are designed in LLM4CBI. (1) LLM4CBI utilizes a program complexity-guided prompt production component, which leverages data and control flow analysis to identify the most valuable variables and locations in programs for mutation. (2) LLM4CBI employs a memorized prompt selection component, which adopts reinforcement learning to select specialized prompts to avoid repeating the same mistakes during the mutation process. Compared with the state-of-the-art approaches (DiWi and RecBi) over 120 real bugs from the two most popular C open-source compilers, namely GCC and LLVM, our evaluation demonstrates the advantages of LLM4CBI. It isolates more bugs, ranging from 13.6% to 90.9% in various settings, than the other approaches. Additionally, we demonstrate that LLM4CBI is extensible, allowing for easy integration with other LLMs.

Index Terms—Software Debugging, Bug Isolation, Compilers, GCC, LLVM, Reinforcement Learning, Large Language Models (LLMs)

# 1 INTRODUCTION

C OMPILERS serve a fundamental role in building reliable software systems, and bugs in compilers can have catastrophic consequences [1], [2]. To mitigate such threats, a crucial task is to isolate the bugs promptly and effectively. However, isolating compiler bugs poses significant challenges due to the limited debugging information. A prevalent direction for resolving the problem is to transform the bug isolation problem into a test program mutation problem [3], [4]. The core idea behind such approaches is first to generate a set of passing test program mutants by mutating the given failing test program and then collect the passing and failing spectrum. Finally, combined with notable Spectrum-based Fault Localization (SBFL) techniques, suspicious files are ranked.

However, existing program mutation strategies in DiWi [3] and RecBi [4] exhibit limitations in terms of effectiveness and demand substantial human effort. First, these strategies are limited in generating diverse test programs. DiWi

only supports the local mutation, such as changing the type of a variable. Although RecBi supports more mutation strategies, such as structural mutation, i.e., changing the control flow of the program, it can only synthesize statement conditions ingredients without statement body (see more details in Section 2.2). Moreover, the random selection of variables and locations for mutation in both DiWi and RecBi is limited by the diversity of the generated test programs. Second, the mutation process in DiWi and RecBi requires significant human effort. Before mutation, DiWi and RecBi require manual code additions to collect necessary context information, and RecBi necessitates the construction of ingredients from existing test programs. Additionally, these strategies pay insufficient attention to the validity of the generated programs that contain undefined behaviors, thereby reducing their effectiveness of bug isolation. Overall, these limitations in ineffective mutation and the associated human effort emphasize the need for improved program mutation strategies in bug isolation.

Inspired by the recent progress of pre-trained Large Language Models (LLMs) (e.g., ChatGPT [5]), in code generation, we propose LLM4CBI, i.e., pre-trained Large Language Models for Compiler Bug Isolation. Our key insights are that (1) LLMs were trained by ultra-large-scale code, so the test programs produced by LLMs tend to be diverse; (2) LLMs have a good learning & reflection mechanism to help generate better outputs based on the users' feedback following a prompt-response dialog paradigm; (3) prompts used by LLMs can be expressed in a natural language, easier for users to use and reducing the human effort to finish a task. Thus, adapting LLMs to generate effective test programs could be promising. However, directly using

<sup>\*</sup> *He Jiang is the corresponding author.* 

H. Tu is with the School of Software, Dalian University of Technology, Dalian, China. H. Tu is also with the School of Computing and Information Systems, Singapore Management University, Singapore. E-mail: haoxintu@gmail.com.

Z. Zhou and H. Jiang are with the School of Software, Dalian University of Technology, Dalian, China, and Key Laboratory for Ubiquitous Network and Service Software of Liaoning Province. H. Jiang is also with DUT Artificial Intelligence, Dalian, China. E-mail: jianghe@dlut.edu.cn, cszide@gmail.com.

I. Yusuf, Y. Li, and L. Jiang are with the School of Computing and Information Systems, Singapore Management University, Singapore. E-mails: imamy.2020@phdcs.smu.edu.sg, liyuxianjnu@gmail.com, lxjiang@smu.edu.sg.

LLMs to generate effective test programs for compiler bug isolation presents several difficulties, raising the following two challenges that need to be addressed.

Challenge 1: Formulation of Precise Prompts. The quality of prompts plays a crucial role in unleashing the program mutation capabilities of LLMs [6], but using existing natural mutation descriptions as prompts may not be effective. For example, the mutation rule "insert an if statement" is a mutation description used in existing work RecBi [4]. Such description lacks precision on *which* variables to use and where to insert the statement, limiting the possibility of mutating failing test programs (i.e., those that can trigger the bug) into passing ones (i.e., those that can not trigger the bug). Due to the difficulties in selecting precise variables and locations, the existing approaches DiWi [3] and RecBi [4] randomly select them, which is shown to be ineffective (see more evaluation results in Section 4.4). Therefore, it is necessary to formulate precise mutation prompts to assist LLMs in generating effective test programs.

*Challenge 2: Selection of Specialized Prompts.* When several prompts are collected, selecting the specialized ones for mutating specific failing test programs is important and challenging. The reasons are two-fold. First, compiler bugs tend to be different and have different language features. One prompt may be useful for mutating one particular failing test program but may not be helpful for another failing test programs may be ineffective (see more evaluation results in Section 4.4). Second, LLMs may make different mistakes when mutating different test programs, and different feedback prompts should also be given to different test programs. Therefore, a new prompt selection strategy is needed to select specialized prompts.

To overcome the above challenges, three new components are designed in LLM4CBI to tame LLMs for generating effective test programs for compiler bug isolation. First, a precise prompt production component is designed to address the first challenge. A precise prompt pattern that could accurately represent the desired mutation operations is first introduced. Then, program complexity metrics measured data and control flow analysis are utilized to identify the most relevant variables and optimal insertion locations. Second, two new components, i.e., a memorized prompt selection component and a lightweight test program validation component, are proposed for selecting specialized prompts. In the prompt selection component, LLM4CBI incorporates memorized search via reinforcement learning to track and accumulate rewards based on the performance of LLMs, which allows LLM4CBI to continually select the specialized prompts for mutating specific test programs. In the test programs validation component, LLM4CBI leverages a static analysis to detect and filter out potential invalid test programs that may contain undefined behaviors, thus mitigating the risks associated with invalid programs.

Empirical evaluations over 120 real bugs from the two most popular C open-source compilers, i.e., GCC and LLVM, are conducted to demonstrate the effectiveness of LLM4CBI. First, we have compared LLM4CBI with two state-of-the-art approaches (i.e., DiWi [3] and RecBi [4]) in terms of compiler bug isolation capabilities. The results show LLM4CBI can isolate 90.91%/35.14% and 50.00%/13.64% more bugs than DiWi and RecBi within Top-1/Top-5 ranked results, respectively. Second, we have evaluated the effectiveness of three new components of LLM4CBI, and the results show that all the components contribute to the effectiveness of LLM4CBI. Third, we show that LLM4CBI is extensible to integrate with other LLMs.

**Contributions.** We make the following contributions:

- To our knowledge, LLM4CBI is the first work aiming to leverage the capabilities of LLMs for compiler bug isolation tasks in the field.
- Three new components, i.e., precise prompt production, memorized prompt selection, and lightweight test program validation, are proposed to guide LLMs to generate effective test programs for compiler bug isolation.
- Empirical evaluations are conducted to demonstrate the effectiveness of LLM4CBI. The results show that LLM4CBI is effective for compiler bug isolation and is extensible to other LLMs.
- LLM4CB1<sup>1</sup> paves the way for future research in compiler bug isolation, opening exciting opportunities to further explore and leverage the capabilities of LLMs for more efficient and effective bug isolation techniques.

**Organizations.** Section 2 gives the background and our motivation. Sections 3 describe the design of LLM4CBI. Section 4 presents the implementation and the evaluation results. Section 5 and 6 discuss the limitations of our approach and threats to validity. Section 7 describes related work, and Section 8 concludes with future work.

# **2** BACKGROUND AND MOTIVATION

In this section, we first give the background about test program mutation for compiler bug isolation and Large Language Models (LLMs). Then, we use an example to illustrate the limitations of existing approaches and highlight the advantages of our approach.

## 2.1 Background

## 2.1.1 Test Program Mutation for Compiler Bug Isolation

Fig. 1 exemplifies the prevalent workflow of existing compiler bug isolation approaches [3], [4]. Given a failing test program that can trigger the compiler bug, existing approaches first use different mutation strategies to produce a passing test program that does not trigger any bug. Then, both the failing and passing test programs are subjected to compilation, enabling the collection of code coverage information of the compiler source files. All the compiler files that are touched by a failing test program during compilation are considered suspicious. Conversely, the passing test program serves to mitigate suspicions regarding innocent files that may have been implicated. To eventually isolate the buggy files, following the well-established principles of Spectrum-Based Fault Localization (SBFL) [7], [8], they compare the execution traces (or spectra) between failing test programs and passing test programs using a formula such as Ochiai [7]. Two recent studies, i.e., DiWi [3] and

1. We plan to release the source code of LLM4CBI in https://github. com/haoxintu/LLM4CBI after the acceptance of this paper.



Fig. 1. General workflow of existing compiler bug isolation

RecBi [4], follow the same strategy, and their goal is to generate a set of programs that have slightly different controland data-flow information compared with the falling test program to flip the compiler execution results (i.e., from failing to passing). We aim to achieve the same goal by leveraging a new approach based on LLMs in this study.

#### 2.1.2 Large Language Models (LLMs)

Recently, pre-trained Large Language Models (LLMs) such as ChatGPT [5] have become ubiquitous and have exhibited remarkable performance in numerous tasks, such as machine translation [9], text summarization [10], classification [11] and code generation [12]. Technically, LLMs can be directly employed to tackle specific downstream tasks by providing the task description to the model, which is known as prompt, without fine-tuning on specialized datasets. This is achieved through a technique known as prompt engineering [13], [14], [15]. Prompt engineering aims to find the prompt that yields the best performance on specific tasks. Prior studies show that prompt engineering can achieve state-of-the-art performance on various downstream tasks [16], [17]. Benefiting from the huge potential of LLMs, there are increasing recent works showing that LLMs can be used for solving different tasks in software engineering tasks [6], [15], [18], [19], [20]. In this study, we aim to unleash the power of LLMs in the field of test program generation tasks.

Many existing LLMs adopt the decoder of the Transformer architecture [21]. Given a prompt containing the task description, the decoder generates the test programs Y as a sequence of tokens, token-by-token by following Equation 1,

$$y_t = \arg\max_{u} P(y|p, y_{< t}) \tag{1}$$

where  $y_t$  is the current token to be predicted,  $y_{<t}$  refers to all the previously predicted tokens, and p is the input prompt. The equation states that the current token  $y_t$  to be predicted is determined by selecting the token y that maximizes the conditional probability  $P(y|p, y_{<t})$ , given the prompt p and the previously generated tokens  $y_{<t}$ . Because a generated test program Y depends on the input prompt pand the search space for the input prompt p is huge, finding the best prompt p to generate the effective test program Y can be challenging. In this work, we propose LLM4CBI to automatically find the prompt p that can generate more effective test programs Y for the compiler bug isolation task.

Two main categories of LLMs are available to the community for code generation tasks: infiling and general [12], [18], [20], [22]. Infilling models (e.g., CodeGen [23], Incoder [24], and PolyCoder [25]) are used to insert the most natural code based on bi-directional context (e.g., in the middle of a code snippet), while general models (e.g., LLaMA [26],



Fig. 2. LLVM bug #16041 (the highlighted gray code in (b) is generated by LLM4CBI)

Alpaca [27], ChatGPT [5], Vicuna [28], and GPT4ALL [29]) target to generate a complete code snippet given the left context only by a natural language description. In this study, we consider general models mainly due to the fact that general models follow the prompt-response dialog paradigm, which involves minimal human effort and fits our objective.

#### 2.2 Motivating Example

Fig. 2(a) showcases a failing test program that exposes a bug in the LLVM-3.4 compiler at the -O3 optimization level. The program introduces a division by zero in the *induction variable elimination* optimization pass in LLVM, causing the miscompilation bug. Notably, Fig. 2(b) represents a passing test program generated by our proposed solution (LLM4CBI), which can not trigger the bug in the LLVM compiler. Next, we show the limitation of existing approaches and the advantages of our approach in generating the passing test program.

#### 2.2.1 Limitations in Existing Approaches

Existing approaches, such as DiWi [3] and RecBi [4], face limitations in generating the above passing test programs due to three primary reasons. First, the mutation strategies employed in DiWi and RecBi exhibit certain limitations. For instance, DiWi only supports local mutation operators that do not alter the control flow of the failing test program. Consequently, it cannot generate crucial elements such as the highlighted gray if statement "if (a == 0)" shown in Fig. 2(b). Similarly, RecBi allows the insertion of structural conditions, like "if (a == 0)", but lacks the capability to generate the corresponding statement bodies, such as "s = v;". Moreover, both DiWi and RecBi rely on a random selection strategy for determining which variables to use and where to insert them during the mutation process, leaving the transformation outcomes largely dependent on chance. Second, the mutation process involved in existing



Fig. 3. Overview design of LLM4CBI

approaches necessitates substantial human effort. Prior to mutation, additional code must be written to collect essential contextual information (e.g., the names of variables like s, a, b, c and their defined types) and extract relevant elements (e.g., if statements) from the existing test programs. Manual coding is required to randomly determine suitable locations for inserting the new code snippets into the failing test programs during the mutation. Third, they pay little attention to the validity of generated test program, which can have the side effect of compiler bug isolation. In summary, the aforementioned limitations underscore the ineffectiveness and high demand of human efforts of existing approaches in generating high-quality test programs. These challenges highlight the need for a new solution that overcomes these shortcomings and effectively generates passing test programs.

#### 2.2.2 Advantages of Our Approach

Compared to DiWi [3] and RecBi [4], LLM4CBI excels in generating effective passing test programs by taming the capabilities in LLMs. First, a precise prompt such as "Please generate a variant program P of the input program F by inserting an if statement and reusing the variables in the list {a, s, v} between lines 12-18" is produced to guide LLM in mutating the given program following certain requirements. Instead of using a vague prompt, LLM4CBI considers more detailed information in the program that can increase the likelihood of flipping from failing to passing to construct a precise prompt. In this way, the new test program is generated by LLM4CBI via inserting the new if-statement shown in gray in Fig. 2(b). Notably, LLM4CBI supports the insertion of bodies (such as "s = v;") in structural mutation, which increases the diversity of the generated test program. Second, benefiting from the LLMs' prompt-response dialog paradigm, the whole mutation process only involves little human effort compared with previous studies. In addition, LLM4CBI detects and filters potential invalid test programs that contain undefined behaviors, further boosting the capabilities of LLM4CBI in terms of compiler bug isolation.

# 3 THE DESIGN OF LLM4CBI

**Overview.** Fig. 3 illustrates the general workflow of LLM4CBI, which address the two main challenges and leverages the capabilities of LLMs to generate effective

test programs for compiler bug isolation. LLM4CBI first generates precise prompts and collects all the generated prompts (1) in the precise prompt production component. Then, LLM4CBI selects a prompt (2) via a memorized prompt selection component and utilizes it as input for the LLMs (3). Next, the LLM4CBI produces a new test program (**4**), which undergoes a **test program validation component** (**⑤**). If the generated program is valid, it is compiled (6), and coverage information of compiler source files is collected. Also, the quality of the generated test program will be measured with similarity and diversity metrics in (**⑦**), which are served as the input of memorized prompt selection component to help select better prompts. However, if the program is invalid due to semantic errors, LLM4CBI provides the feedback (8) prompts to the LLMs, guiding them not to make the same mistakes again. Ultimately, upon reaching the termination condition (e.g., 1 hour), LLM4CBI employs SBFL along with the failing and passing spectra to rank suspicious files (**9**). Specifically, the precise prompt production component is designed to address the first challenge of the formulation of precise prompts, and two other components, i.e., memorized prompt selection component and lightweight test program validation component, are utilized to tackle the second challenge of the selection of specialized prompts. We provide further details regarding this in the subsequent sections.

## 3.1 Precise Prompt Production

This section presents the precise prompt production component, which addresses the first challenge of the formulation of precise prompts. We first outline the design of the prompt production pattern for LLMs and then show how to utilize program complexity metrics, e.g., data-flow and controlflow complexity, to populate the pattern.

## 3.1.1 Prompt Pattern for Program Mutation

The following is the pattern designed in LLM4CBI for constructing effective prompts for LLMs.

*Pattern:* Please generate a variant program **P** of the input program **F** by <mutation rule > and reusing the <variables > between <location >.

In the pattern, P refers to the newly generated test program, and F refers to the given failing test program. In

the rest, <mutation rule > means the actual mutation operation; <variables > and <location > describe the specific requirements when conducting the mutation.

We reuse the existing mutation rules (cf Table 1) in the pattern. Since compilers use different strategies to optimize the programs that have different data or control flow [2], our intuition is that, instead of randomly mutating programs in existing approaches, *mutating the most complex part of the failing program is more likely to flip the failing into passing*. To this end, LLM4CBI measures the most complex part by two means: the variable that holds complex data flow and the location that involves complex control flow.

## 3.1.2 Data-flow Complexity-guided Variable Selection

The data-flow analysis aims to output the most complex variables defined and used in the given failing test program.

Due to the fact that we aim to investigate the complexity of a variable by examining how this variable can affect and to what extent, we deem that the more a variable is defined (or assigned), the more complex dependence is held on the variable, thus contributing to the data-flow complexity.

Following the existing definition of data-flow complexity [30], we follow the existing work [31] and opt for the variable *def-use* chain [32] to analyze the data-flow complexity of a program. Specifically, we calculate the complexity of a variable ( $Comp_{var}$ ) by the following Equation:

$$Comp_{var} = N_{def} + N_{use} \tag{2}$$

where the  $N_{def}$  counts the number of times that a variable is defined, including redefining or assigning. Note that *Def* keeps track of the changes in a variable, so the data dependency analysis is included.  $N_{use}$  counts the number of times that a variable is used. This refers to the value of a variable value being used in some computation with no modification to the variable's value. Under the above Equation, the data flow analysis upon the failing test program in Fig. 2(a) will produce a variable list {a, s, v}, which represents the Top-3 complex variables used in the program.

## 3.1.3 Control-flow Complexity-guided Location Selection

The aim of the control-flow analysis is to output the location of the most complex statement in the program. We leverage the control-flow graph of the input failing program, where each node represents the statement and the edge indicates the execution flow. When the Control-Flow Graph (i.e., CFG) is available, we calculate the complexity of each statement using the following Equation (3) based on cyclomatic complexity [30]:

$$Comp_{control} = N_{eage} - N_{node} + 2 \tag{3}$$

where  $N_{eage}$  and  $N_{node}$  represent the number of edges and nodes in the CFG, respectively. Since the cyclomatic complexity is not designed to measure the complexity at the statement level, we count the complexity of each statement by obtaining the complexity values during cyclomatic complexity calculation. Note that we intentionally ignore the statement that includes the oracle (i.e., having the printf or abort function). The reason is that changing the code block, including the test oracle, is more likely to break the oracle, meaning a fake passing test program is probably

TABLE 1 Mutation rules applied in the prompt pattern

| ID | Rule   |
|----|--|
| 1  | inserting an if statement                                      |
| 2  | inserting a loop (i.e., while or for) statement                |
| 3  | inserting a function call                                      |
| 4  | inserting a goto statement                                     |
| 5  | inserting a qualifier (i.e., volatile, const, and restrict)    |
| 6  | removing a qualifier (i.e., volatile, const, and restrict)     |
| 7  | inserting a modifier (i.e., long, short, signed, and unsigned) |
| 8  | removing a modifier (i.e., long, short, signed, and unsigned)  |
| 9  | replacing a constant with another valid one                    |
| 10 | replacing a binary operator with another valid one             |
| 11 | removing a unary operator on the variables                     |
| 12 | replacing a unary operator on the variables                    |
| 13 | replacing a variable with another valid one                    |

generated [3], [4]. Taking the code example shown in Fig. 2(a) again, the control-flow analysis designed in LLM4CBI will indicate that the most complex control flow lies in the for loop between Lines 12 - 18. In this way, after getting the variable list and the desired location to be inserted, LLM4CBI generates certain prompts based on the designed pattern. For example, one of the generated prompts is:

"Please generate a variant program P of the input program F by <inserting an if statement > and reusing the <variables in the list  $\{a, s, v\}$  > between lines 12-18 > ".

As aforementioned in Section 1, not every prompt contributes equally to a specific failing test program. Furthermore, LLMs may make different mistakes when mutating a program: e.g., LLMs may incur a syntax error in a failing test program but a semantic error in another program. Giving all the error information as feedback prompts is not necessary. Hence, a specialized prompt selection strategy is supported and developed in LLM4CBI.

## 3.2 Memorized Prompt Selection

This subsection and the next subsection present memorized prompt selection and lightweight test program validation components to address the second challenge of the selection of the specialized prompts. In this subsection, we first give the background of reinforcement learning and then detail the memorized prompt selection.

## 3.2.1 Reinforcement Learning

Reinforcement learning (a kind of memorized search) is a field of study that aims to teach an agent how to take actions within an environment in order to maximize its cumulative reward over the long term [33], [34]. Key roles in reinforcement learning include (1) **Agent**: the role of a learner and decision-maker; (2) **Environment**: Everything that is composed of and interacts with something other than the agent; (3) **Action**: The behavioral representation of the agent body; (4) **State**: The information that the capable body obtains from the environment; (5) **Reward**: Feedback from the environment about the action. Reinforcement learning can generally be classified into value-based algorithms (e.g., Deep Q Learning algorithm [35]) and policy-based algorithms (e.g., Policy Gradients algorithm [36]).

With the advancement of reinforcement learning, a class of algorithms known as Actor-Critic (AC) algorithms have been proposed [37], combining elements of value-based and policy-based strategies. In this study, we employ the Advantage Actor-Critic (i.e., A2C [38]) framework to address the challenge of compiler bug isolation, as it is both effective (in comparison to AC [37]) and suitable for single-thread and multi-thread systems (compared to Asynchronous Advantage Actor-Critic, i.e., A3C [38]). In this study, LLM4CBI adopts the A2C (Advantage Actor-Critic) framework [38] to learn the effects of prompt, enabling the generation of effective passing test programs for a specific compiler bug. We opt for the A2C framework mainly because it has demonstrated practical effectiveness, efficiency, and stability with low variance [39], making it a suitable choice.

## 3.2.2 Reinforcement Learning for Prompt Selection

The effectiveness of randomly applying mutations upon a given failing test program can be limited [4]. Consequently, we do not randomly select prompts for LLMs to generate program variants; we need to efficiently generate more effective passing test programs within a given time tailored to a specific compiler bug. To accomplish this goal, we employ reinforcement learning in LLM4CBI, where the quality of the generated passing test programs serves as the reward metric of a prompt.

Fig. 4 provides an overview of the reinforcement learning-based strategy for selecting prompts in LLM4CBI. Following the A2C framework, LLM4CBI first initializes two neural networks: the Actor Neural Network (ANN) and the Critic Neural Network (CNN) in the agent. The ANN predicts the probability distribution of actions based on historical knowledge, enabling the subsequent selection of an optimal action by LLM4CBI. CNN predicts the potential reward that can be accumulated from the current state to a future state after executing the selected action, incorporating future knowledge. LLM4CBI chooses an action  $a_t$  to select a prompt (randomly chosen for the first time) and measure the quality  $(Q_t)$  of the newly generated test program. To facilitate learning, LLM4CBI employs an advantage loss function  $(A_{loss})$  based on the predicted potential reward (PR) and the actual reward (R) obtained from the selected prompt. Finally, LLM4CBI updates the status of all the ANN, CNN, and states to the agent. LLM4CBI repeatedly selects a prompt to generate test programs until the termination condition (e.g., 1-hour limit is reached or 10 program variants are generated) is reached.

Consistent with existing A2C-based approaches [37], [38], both ANN and CNN in LLM4CBI are with a single hidden layer to ensure lightweight and fast convergence. The following provides detailed explanations of the most important parts, including the actual reward and advantage loss function calculations.

**Measuring Actual Reward.** An essential factor contributing to the effectiveness of the A2C-based approach lies in determining the actual reward subsequent to applying a prompt. Drawing the inspiration from previous research [3], [4], a collection of proficient passing test programs needs to meet both *similarity* and *diversity* criteria. The *similarity* entails that each passing test program should exhibit a



\*  $R_t$ : actual reward at time t

\*  $A_{loss}$ : advantage loss function at time t

\*  $m_j$ : a selected prompt  $(j \in \{1, 13\})$ 

Fig. 4. Memorized prompt selection guided by reinforcement learning: The agent uses an ANN to predict an actor  $a_t$  (i.e., a prompt  $m_j$  used for mutating a program). After obtaining the new test program from LLMs, the environment calculates the actual reward  $R_t$  based on the quality  $(Q_t)$  of the newly generated test program. In the meantime, CNN in the agent predicts a potential reward  $PR_t$ . Next, the advantage loss  $(A_{loss})$  is measured by combing the actual reward and potential reward. Later, the weight (w) of ANN and CNN and state  $(s_t)$  will be updated to the agent generate a better prompt.

comparable compiler execution trace to that of the given failing test program. Consequently, following the principles of SBFL, the suspicion associated with a greater number of buggy-free files can be diminished. The *diversity* requires that different passing test programs possess distinct compiler execution traces from one another to reduce suspicion regarding various buggy-free files. By doing so, aggregating a set of passing test programs that have undergone mutation facilitates the effective isolation of genuinely faulty files by circumventing bias. Both *similarity* and *diversity* rely on the *distance* metric, which is defined as:

$$dist(a,b) = 1 - \frac{Cov_a \cap Cov_b}{Cov_a \cup Cov_b}$$
(4)

where the dist(a, b) represents the coverage distance between two test programs a and b, which is determined using the Jaccard Distance measurement [3].  $Cov_a$  and  $Cov_b$ represent the sets of statements covered in compilers by test programs a and b, respectively.

Denoting the set of generated passing test programs as  $p = \{p_1, p_2, ..., p_n\}$  and the failing test program as f, we formalize the metrics of *similarity* and *diversity* achieved by the set of passing test programs, represented as Equation 5 and Equation 6, respectively.

$$sim = \frac{\sum_{i=1}^{N} (1 - dist(p_i, f))}{N}$$
 (5)

$$div = \frac{\sum_{i=1}^{N-1} \sum_{j=i+1}^{N} dist(p_i, p_j)}{N(N-1)/2}$$
(6)

where N is the number of passing test programs.

At time step *t*, once a passing test program is generated, LLM4CBI evaluates the effectiveness of the current set of

passing test programs by linearly combining the attained measures of *similarity* and *diversity* in Equation 7.

$$Q_t = n(\alpha \times div_t + (1 - \alpha) \times sim_t) \tag{7}$$

where the coefficient  $\alpha$  represents the weighting factor for the linear combination of *diversity* and *similarity* in Equation 7. Additionally, following the existing study [4], Equation 7 also incorporates another coefficient *n*, which corresponds to the size of the set of passing test programs.

Subsequently, LLM4CBI determines whether to accept the generated passing test program based on whether it can enhance the overall quality of the set of passing programs compared to the previous time step denoted as t - 1. The Equation 8 outlines the computation of the enhanced quality relative to the previous time step.

$$\triangle Q_t = Q_t - Q_{t-1} \tag{8}$$

Nevertheless, in each state, only one prompt is chosen to generate a passing test program, and the performance of a prompt can vary significantly depending on different bugs. To balance the influence of the diverse performance of prompts, LLM4CBI incorporates both the current time step improvement and the historically accumulated improvement attributed to the current prompt. This combined value serves as the actual reward obtained at the current time step, which is defined as follows:

$$R_t = \frac{\sum_{i=1}^t \triangle Q_i}{T(m_i)} \tag{9}$$

Here,  $T(m_j)$  represents the count of times the  $m_j$  (a prompt) has been chosen to mutate the failing test program.  $\triangle Q_i$ is defined as zero ( $\triangle Q_i = 0$ ) if the selected prompt at the  $i^{th}$  time step is not  $m_j$ ; if the selected prompt is  $m_j$ ,  $\triangle Q_i$ is computed using Equation 8. Whether selecting a new prompt  $m_j$  or previously selected prompt  $m_j$  depends on the decision made by ANN in the agent.

**Calculating Advantage Loss.** While the actual reward  $(R_t)$  is obtained at the current time step t, LLM4CBI also utilizes CNN to predict the potential reward  $(PR_{t+i})$ . To effectively consider future factors, A2C incorporates an advantage loss function. This function is designed to address the issue of high variance in the two neural networks and prevent convergence towards local optima [38]. The advantage loss function is expressed as follows in Equation 10:

$$A_{loss}(t) = \sum_{i=t}^{t+u} (\gamma^{i-t} R_i) + \gamma^{u+1} P R_{t+u} - P R_t$$
(10)

the variable u indicates that the CNN considers the future u consecutive states and actions when predicting the potential reward.  $\gamma$  represents the weight assigned to the actual future reward.  $PR_{t+u}$  and  $PR_t$  denote the predicted potential rewards at the  $(t + u)^{th}$  and  $t^{th}$  time steps, respectively, as determined by CNN. Notably, LLM4CBI repeats this process for u times within a time step to approximate the actual future reward.

Using the loss computed by the advantage function in Equation 10, LLM4CBI proceeds to update the weights of both the ANN and CNN following Equation 11.

$$w = w + \beta \frac{\partial (\log P_w(a_t|s_t) A_{loss}(t))}{\partial w}$$
(11)

where  $s_t$  represents the current state, while  $a_t$  denotes the corresponding action.  $P_w(a_t|s_t)A_{loss}(t)$  represents the probability of performing action  $a_t$  at state  $s_t$  based on the parameters w in both the ANN and CNN.  $\beta$  represents the learning rate of the weight updates.

# 3.3 Lightweight Test Program Validation

Existing studies [3], [4] pay little attention to the validity of the mutated test programs. First, the test programs generated by these approaches may contain undefined behaviors. As demonstrated in our evaluation results in Section 4.4, such test programs reduce the effectiveness of compiler bug isolation. Second, existing approaches may generate test programs that do not have a test oracle, which can also affect the effectiveness of bug isolation. Third, existing studies are unaware of the errors they made during the mutation process, so they frequently make the same mistakes when mutating test programs.

To address the above limitations, LLM4CBI designs a semantic validation to filter away semantically invalid test programs and utilizes a test oracle validation to fix the test programs that violate test oracles. Additionally, LLM4CBI collects all the validation errors in the test programs generated by LLMs and gives such information as feedback prompts to LLMs to avoid repeating the same mistakes. Next, we detail the validation processes.

## 3.3.1 Program Semantic Validation

We chose static analysis checks on the newly generated test program that may contain any undefined behavior, which proved to be lightweight compared with dynamic analysis approaches [40]. As shown in step **⑤** in Fig. 3, the newly generated test program is transferred to this component for checking the semantic validity. Based on the analysis capabilities from Frama-C [40], we opt for five different categories of undefined behaviors in LLM4CBI:

- memem\_access: invalid memory access, such as out-ofbound read or out-of-bound write.
- shift: invalid RHS (Right-Hand Shift) or LHS (Left-Hand Shift) operand for right or left shift operation.
- index\_bound: accessing out-of-bounds index of an array.
- initialization: accessing uninitialized left-value, i.e., use a variable before it was uninitialized.
- division\_by\_zero: a number is divided by zero.

If one of the above undefined behaviors is detected, the semantic error information will be updated to LLMs to avoid repeating the same mistakes. For example, if a new test program contains an undefined divided by zero behavior, an additional prompt, "The above program contains an undefined behavior divided by zero, please do not generate such test programs again.", will be fed to LLMs in step **§**.

## 3.3.2 Test Oracle Validation

**Test Oracles**. It is also required to check whether a generated test program is passing or failing [3], [4], [41], [42]. According to the types of compiler bugs (i.e., crash bugs and wrong-code bugs), following the existing work [3], [4], LLM4CBI considers two types of test oracles: (1) Regarding crash bugs (i.e., the compiler crashes when using some compilation options to compile a test program), the test

oracle is whether the compiler still crashes when using the same compilation options to compile a generated test program. (2) Regarding wrong-code bugs (i.e., the compiler mis-compiles a test program without any failure messages, causing the test program to have inconsistent execution results under different compilation options), the test oracle is whether a generated test program still produces inconsistent execution results under the compilation options producing the previous inconsistencies. Similar to DiWi [3] and RecBi [4], LLMs may not put in the test oracles in a generated test program; so, we apply another heuristic validation to check for missing oracles. E.g., we check if the generated test program contains the same number of abort or printf statements as the given failing test program.

If a newly generated test program passes the above validations, the buggy compiler is used to compile the generated test program in step **③**. LLM4CBI collects the semantic error or test oracle information and uses it as feedback prompts to guide LLMs not to generate programs with the same kinds of errors. It is worth noting that since different test programs may contain different kinds of errors, the feedback prompts could be different.

## 3.4 Suspicious Files Ranking

LLM4CBI utilizes the concept of SBFL (Spectrum-Based Fault Localization) to identify potentially buggy compiler files by comparing the coverage of failing and passing tests in **9**, as outlined in previous research [3], [4]. To be specific, since Ochiai [7] perform well, LLM4CBI employs the Ochiai Equation  $score(s) = \frac{ef_s}{\sqrt{(ef_s + nf_s)(ef_s + ep_s)}}$  to calculate the suspicious score of each statement. In the Equation,  $ef_s$  and  $nf_s$  represent the number of failing tests that execute and do not execute statement s, and  $ep_s$  represents the number of passing tests that execute statement s. In LLM4CBI, since there is only one given failing test program, the number of failing tests that execute statement s  $(ef_s)$  is fixed at 1. Additionally, LLM4CBI focuses solely on the statements executed by the given failing test program, implying that the number of failing tests that do not execute statement  $s (nf_s)$  is 0. As a result, the Ochiai Equation is simplified to:  $score(s) = \frac{1}{\sqrt{(1+ep_s)}}$ . Once the suspicious score of each statement is obtained, LLM4CBI proceeds to calculate the suspicious score of each compiler file. Similar to previous research [3], [4], LLM4CBI aggregates the suspicious scores of the statements executed by the given failing test program within a compiler file to determine the suspicious score of the file  $SCORE(f) = \frac{\sum_{i=1}^{n_f} score(s_i)}{n_i}$ . The number of statements that the failing test program executes in the compiler file f is denoted as  $n_f$ . LLM4CBI utilizes this information to calculate the suspicious score of each compiler file. By arranging the compiler files based on their suspicious scores in descending order, LLM4CBI yields a ranking list.

#### 4 EVALUATION

## 4.1 Experimental Setup

**Implementation of LLM4CBI.** LLM4CBI was implemented utilizing OClint [43] (v22.02), srcSlice [31] (v1.0), Gcov [44] (v4.8.0), and PyTorch [45] (v1.10.1+cu113). OClint is served

to calculate the cyclomatic complexity of each statement; srcSlice is used to get the data-flow complexity of the variables defined and used in the program; Gcov is applied for collecting compiler coverage information; PyTorch supports the A2C framework. For A2C, we set the hyperparameters with the default settings in the previous study [4]. For the implementation of test program validation, we adopt Frama-C [40] (Phosphorus-20170501) to check the semantic validity of the test program, and we write Python scripts (python 3.8.5) to check if there are any test oracle violations. We adapt GPT-3.5 as the default LLMs in LLM4CBI, with the *temperature* parameter 1.0 in GPT-3.5 (see more detailed discussions on temperature settings in Section 5).

**Study Subjects**. We use GCC and LLVM as our subjects to assess the effectiveness of LLM4CBI. Both two compilers are widely used in existing literature [3], [4], [41], [42], [46], [47], [48] and therefore constitute a comprehensive evaluation. On average, a GCC buggy version contains 1,758 files with 1,447K source lines of code (SLOC), while an LLVM buggy version comprises 3,265 files with 1,723K SLOC.

**Benchmark**. We utilize a benchmark consisting of 120 real compiler bugs, with an equal distribution of 60 GCC and 60 LLVM bugs, which includes all bugs studied in prior works [3], [4]. Specifically, each bug is accompanied by relevant buggy details, including the faulty compiler version, the failing test program, the buggy compilation options, and the faulty files which serve as the ground truth.

**Running Platform**. We conduct all the experiments on a workstation equipped with a 12-core CPU, Intel(R) Xeon(R) W-2133 CPU @ 3.60GHz, 64G RAM, and Ubuntu 18.04 operating system, without GPU support.

**Evaluation Metrics.** Each approach for isolating compiler bugs generates a list of suspicious compiler files. To evaluate the effectiveness of each approach, we measure the position of each buggy file in the ranking list with the help of the ground truth. In cases where multiple compiler files had the same suspicious scores, we follow the precedent set by prior research [49], [50] and assign the worst ranking. Specifically, we compute the following metrics commonly used in compiler bug isolation studies [3], [4], [41], [42].

- **Top-N**. This metric denotes the number of bugs that are effectively isolated and contained within the Top-N position, where N is a member of the set 1, 5, 10, 20 as specified in our study. A higher value of Top-N indicates a better performance of an approach.
- Mean First Ranking (MFR). This metric represents the average rank of the first faulty file within the ranking list for each bug. The objective of MFR is to promptly isolate the initial defective element in order to expedite the debugging process. A smaller value is better, as it indicates that developers could localize the corresponding bug as quickly as possible.
- Mean Average Ranking (MAR). This metric measures the average of the mean rank of every faulty file within the ranking list for each bug. The MAR metric is intended to isolate all faulty elements accurately. Similar to MFR, the approach with a smaller value of MAR is better.

TABLE 2 Compiler bug isolation effectiveness comparison with two state-of-the-art approaches (under Setting-1 in RQ1)

| Subject | Approach                         | Num.<br>Top-1 | $\stackrel{\Uparrow_{Top-1}}{(\%)}$ | Num.<br>Top-5  | $\stackrel{\Uparrow_{Top-5}}{(\%)}$ | Num.<br>Top-10 | $ \stackrel{\Uparrow Top-10}{(\%)} $ | Num.<br>Top-20                             | ↑ <i>Top</i> -20<br>(%) | MFR                     | ↑ <sub>MFR</sub><br>(%) | MAR                     | ↑ <i>MAR</i><br>(%) |
|---------|----------------------------------|---------------|-------------------------------------|----------------|-------------------------------------|----------------|--------------------------------------|--|-------------------------|-------------------------|-------------------------|-------------------------|---------------------|
| GCC     | DiWi [3]                         | 7             | 57.14                               | 19             | 36.84                               | 32             | 18.13                                | 43   | 16.28                   | 22.60                   | 42.92                   | 22.93                   | 40.25               |
|         | RecBi [4]                        | 8             | 37.50                               | 24             | 8.33                                | 36             | 13.89                                | 45   | 11.11                   | 19.67                   | 34.42                   | 20.13                   | 31.94               |
|         | LLM4CBI                          | 11            | -                                   | 26             | -                                   | 41             | -                                    | 50   | -                       | 12.90                   | -                       | 13.70                   | -                   |
| LLVM    | DiWi [3]<br>RecBi [4]<br>LLM4CBI | 4<br>6<br>10  | 150.00<br>66.67<br>-                | 21<br>23<br>24 | 33.33<br>20.00<br>-                 | 27<br>29<br>33 | 22.22<br>13.79<br>-                  | $\begin{array}{c} 40\\ 44\\ 48\end{array}$ | 20.00<br>9.09<br>-      | 27.05<br>24.65<br>13.73 | 49.24<br>44.30<br>-     | 27.06<br>24.70<br>13.90 | 48.63<br>43.72<br>- |
| ALL     | DiWi [3]                         | 11            | 90.91                               | 41             | 35.14                               | 59             | 25.42                                | 83   | 18.07                   | 24.83                   | 46.36                   | 25.00                   | 44.79               |
|         | RecBi [4]                        | 14            | 50.00                               | 45             | 13.64                               | 65             | 13.85                                | 89   | 10.11                   | 21.16                   | 39.91                   | 21.42                   | 38.43               |
|         | LLM4CBI                          | 21            | -                                   | 48             | -                                   | 74             | -                                    | 98   | -                       | 13.32                   | -                       | 13.80                   | -                   |

Note: Columns "↑ \*" present the improvement rates (%) of LLM4CBI over the compared approaches in terms of various metrics.

#### 4.2 Research Questions

In this study, we aim to answer the following main research questions (RQs):

- **RQ1**: Can LLM4CBI outperform state-of-the-art approaches (i.e., DiWi [3] and RecBi [4]) in terms of the effectiveness and efficiency of compiler bug isolation?
- **RQ2**: Can each main component, i.e., precise prompt production, memorized prompt selection, and lightweight test program validation, contribute to LLM4CBI?
- **RQ3**: Can LLM4CBI be easily extended with other LLMs for the compiler bug isolation task?

## 4.3 Answers to RQ1

#### 4.3.1 Experimental Settings

We set up the following two settings to investigate RQ1:

- Setting-1: terminate with the same running time (i.e., one hour). This is the standard comparison strategy used in existing compiler bug isolation studies [3], [4], [41], [42] for evaluating their effectiveness.
- Setting-2: terminate when generating the same number (i.e., 10) of passing test programs. This setting aims to demonstrate the efficiency of LLM4CBI further. We opt for the number suggested by the existing empirical studies [7]. We gave the timeout of 2 hours if an approach can not generate the desired number of test programs of a bug. We add this setting because during the experiments in Setting-1, we find the number of generated passing test programs by comparative approaches is different, and LLM4CBI could generate a larger number of passing test programs. Thus, whether the superior performance on LLM4CBI benefited from the more test programs or the quality of the newly generated programs is unknown. We conduct Setting-2 to investigate it further.

**Comparison Strategies**. For both settings, we repeatedly run all the comparative approaches three times and calculated the median results of Top-N, MFR, and MAR metrics to reduce the influence of randomness. Additionally, for Setting-2, we compare the execution time for each approach and speedups achieved by LLM4CBI.

#### 4.3.2 Experimental Results

**Results for Setting-1**. The comparison results of Setting-1 are presented in Table 2. The first column represents

subject compilers, and the second column shows different approaches. Columns 3-10 provide the Top-N metrics derived from the median values obtained from three iterations of each approach, including the number of Top-N (i.e., **Num. Top-N**) and improvements (i.e.,  $\uparrow_{Top-N}$  (%)) made by LLM4CBI. Columns 11-14 represent the **MFR** (Mean First Ranking) and **MAR** (Mean Average Ranking) metrics, as well as the improvements achieved by LLM4CBI.

Notably, LLM4CBI demonstrates its capability by successfully isolating 21, 48, 74, and 98 compiler bugs (out of a total of 120 compiler bugs in GCC and LLVM) within the Top-1, Top-5, Top-10, and Top-20 files, respectively. This accounts for the improvement of 17.50%, 41.67%, 61.67%, and 81.67% than DiWi and 17.50%, 41.67%, 61.67%, and 81.67 than RecBi, respectively. Further analysis of the effects across different subject compilers revealed interesting findings. Despite the larger number of compiler files in LLVM compared to GCC, LLM4CBI exhibited slightly better results in the case of GCC. For instance, LLM4CBI achieved MFR and MAR values of 12.90 and 13.70 for GCC, while corresponding values for LLVM were 13.73 and 13.90.

Compared with DiWi and RecBi, the evaluation reveals that LLM4CBI outperforms DiWi and RecBi across all metrics and for both GCC and LLVM compilers. Notably, LLM4CBI demonstrates significant improvements of 90.91% and 35.14% over DiWi in terms of Top-1 and Top-5. For RecBi, LLM4CBI could isolate 50.00% and 13.64% more bugs than RecBi in terms of Top-1 and Top-5. In particular, the practical significance of the Top-5 metric is highlighted by previous research, which indicates that developers often discontinue the use of automated debugging tools if the faulty elements cannot be localized within the Top-5 positions. Consequently, LLM4CBI shows better practicality compared to DiWi and RecBi by substantially improving the effectiveness of compiler bug isolation, specifically in relation to the Top-5 metric.

Furthermore, in terms of MFR and MAR, LLM4CBI achieves a considerable improvement of 46.36% and 44.79% over DiWi and 39.91% and 38.43% over RecBi, respectively. The improvement of MFR and MAR demonstrates that LLM4CBI can promptly and accurately isolate more compiler bugs than DiWi and RecBi.

**Results for Setting-2**. From Table 3, for all the 120 bugs, we can know that LLM4CBI also outperforms comparative

TABLE 3 Compiler bug isolation effectiveness comparison with two state-of-the-art approaches (under Setting-2 in RQ1)

| Subject | Approach  | Num.<br>Top-1 | $\begin{pmatrix} \uparrow_{Top-1} \\ (\%) \end{pmatrix}$ | Num.<br>  Top-5 | $\stackrel{\Uparrow_{Top-5}}{(\%)}$ | Num.<br>Top-10 | $\stackrel{\Uparrow_{Top-10}}{(\%)}$ | Num.<br>Top-20 | $\stackrel{\Uparrow_{Top-20}}{(\%)}$ | MFR   | $\begin{pmatrix} \uparrow_{MFR} \\ (\%) \end{pmatrix}$ | MAR   | $\mathop{\Uparrow}_{MAR}$ (%) |
|---------|-----------|---------------|--|-----------------|-------------------------------------|----------------|--------------------------------------|----------------|--------------------------------------|-------|--|-------|-------------------------------|
| GCC     | DiWi [3]  | 6             | 33.33  | 20              | 20.00                               | 33             | 6.06                                 | 41             | 7.32                                 | 20.87 | 23.43  | 22.20 | 26.58                         |
|         | RecBi [4] | 7             | 14.29  | 22              | 9.09                                | 34             | 2.94                                 | 42             | 4.76                                 | 18.40 | 13.15  | 18.73 | 12.97                         |
|         | LLM4CBI   | 8             | -  | 24              | -                                   | 35             | -                                    | 44             | -                                    | 15.98 | -  | 16.30 | -                             |
| LLVM    | DiWi [3]  | 5             | 60.00  | 21              | 14.29                               | 29             | 20.69                                | 39             | 10.26                                | 20.61 | 20.61  | 20.86 | 18.12                         |
|         | RecBi [4] | 7             | 14.29  | 23              | 4.35                                | 34             | 2.94                                 | 40             | 7.50                                 | 18.25 | 7.89   | 18.45 | 7.43                          |
|         | LLM4CBI   | 8             | -  | 24              | -                                   | 35             | -                                    | 43             | -                                    | 16.81 | -  | 17.08 | -                             |
| ALL     | DiWi [3]  | 11            | 45.45  | 41              | 17.07                               | 62             | 12.90                                | 80             | 8.75                                 | 20.74 | 20.95  | 21.53 | 22.48                         |
|         | RecBi [4] | 14            | 14.29  | 45              | 6.67                                | 68             | 2.94                                 | 82             | 6.10                                 | 18.33 | 10.53  | 18.59 | 10.22                         |
|         | LLM4CBI   | 16            | -  | 48              | -                                   | 70             | -                                    | 87             | -                                    | 16.40 | -  | 16.69 | -                             |

Note: Columns "↑ \*" present the improvement rates (%) of LLM4CBI over the compared approaches in terms of various metrics.



(a) Distribution of execution time (b) Speedups over DiWi and RecBi

Fig. 5. Performance comparison over DiWi, RecBi, and LLM4CBI (under Setting-2 in RQ1)

approaches: LLM4CBI can isolate more bugs and hold the lowest MFR and MAR.

For the efficiency side, Fig. 5 presents the detailed performance results. The *x-axis* in box Fig. 5(a) show different approaches in GCC and LLVM, and *y-xais* represents the time spent by isolating each bug. For the figures, we can observe LLM4CBI takes less time when isolating most of the bugs. We can see the time taken on LLVM is generally larger than on GCC. This is justifiable as the number of files of LLVM is larger than GCC, and the more files means the more time spent on calculating the coverage. We also calculate the speedups achieved by LLM4CBI. Specifically, we follow the Equation below to calculate the speedups:

$$\frac{T_{baseline} - T_{\text{LLM4CBI}}}{T_{baseline}} \times 100 \tag{12}$$

where  $T_{baseline}$  represents the time spent by the baselines (i.e., DiWi and RecBi) for generating 10 passing test programs on average, and  $T_{LLM4CBI}$  describes the time our proposed LLM4CBI spent generating the same number of passing test programs on average. Fig. 5(b) shows the results. We can see LLM4CBI is able to achieve 53.19% and 64.54% as well as 47.31% and 63.19% than DiWi and RecBi, for GCC and LLVM, respectively.

It is interesting to note that the overall results of LLM4CBI are better in Setting-1 compared with Setting-2. This is reasonable as LLM4CBI could generate more passing test programs in one hour, improving the results. Therefore, we suggest developers run a long time of LLM4CBI to get better isolation results.

Summary for RQ1. The evaluation clearly demonstrates that LLM4CBI significantly outperforms two state-of-the-

art approaches in two different settings: LLM4CBI is able to effectively and efficiently generate passing test programs for compiler bug isolation than DiWi and RecBi.

## 4.4 Answers to RQ2

## 4.4.1 Experimental Settings

We use the following variants of LLM4CBI aiming to differentiate the effects of main components in LLM4CBI:

- LLM4CBI<sub>ep</sub> uses a simple prompt without data flow and control flow analysis. That is, LLM4CBI<sub>ep</sub> only keeps the <mutation rule > and does not rely on the <variables > and <location > information to fill in the designed pattern.
- LLM4CBI<sub>sp</sub> utilizes a specific prompt by giving the "the most complex data and control flow". That means, LLM4CBI<sub>sp</sub> replaces the <variables > with "the most complex variables" and <location > with "in the most complex statements", which depends on the program understanding capabilities of LLMs to fill in the pattern.
- LLM4CBI<sub>rand</sub> randomly selects a prompt without the memorized prompt selection, meaning LLM4CBI<sub>rand</sub> performs a random selection of the prompt during the prompt selection process.
- LLM4CBI<sub>selnov</sub> removes the test program validation component in the prompt selection process in LLM4CBI: LLM4CBI<sub>selnov</sub> does not care about test program validity for compiler bug isolation.

Among these variants, LLM4CBI<sub>ep</sub> and LLM4CBI<sub>sp</sub> aim to investigate whether the new program complexity-guided prompt production pattern is effective, while LLM4CBI<sub>rand</sub> and LLM4CBI<sub>selnov</sub> target to understand whether the memorized prompt selection and test program validation could contribute to LLM4CBI, respectively.

**Comparison Strategies**. We run the four variants with the same strategy as Setting-1 as RQ1. We then compare the Top-N, MFR, and MAR metrics for each approach to articulate the contribution of those components.

#### 4.4.2 Experimental Results

The comparison results between LLM4CBI and the comparative variant approaches are presented in Table 4, where each column and row has the same meaning as in Table 2.

**Contribution of Prompt Production**. As shown in Table 4, LLM4CBI is better than both LLM4CBI<sub>ep</sub> (i.e., the approach

TABLE 4 Compiler bug isolation effectiveness comparison with four variants of LLM4CBI

| Subject | Approach                  | Num.<br>Top-1 | $\begin{pmatrix} \uparrow_{Top-1} \\ (\%) \end{pmatrix}$ | Num.<br>Top-5 | $\begin{pmatrix} \uparrow_{Top-5} \\ (\%) \end{pmatrix}$ | Num.<br>Top-10 | $\stackrel{\Uparrow_{Top-10}}{(\%)}$ | Num.<br>Top-20 | $\stackrel{\Uparrow_{Top-20}}{(\%)}$ | MFR   | $\stackrel{\Uparrow_{MFR}}{(\%)}$ | MAR   | $\mathop{\Uparrow}_{MAR}$ (%) |
|---------|---------------------------|---------------|--|---------------|--|----------------|--------------------------------------|----------------|--------------------------------------|-------|-----------------------------------|-------|-------------------------------|
|         | LLM4CBI <sub>ep</sub>     | 7             | 57.14  | 24            | 8.33   | 36             | 13.89                                | 42             | 19.05                                | 20.87 | 38.19                             | 21.48 | 36.22                         |
|         | LLM4CBI <sub>sp</sub>     | 6             | 83.33  | 23            | 13.04  | 33             | 24.24                                | 39             | 28.21                                | 20.50 | 37.07                             | 24.42 | 43.90                         |
| GCC     | LLM4CBI <sub>rand</sub>   | 6             | 83.33  | 25            | 4.00   | 33             | 24.24                                | 42             | 19.05                                | 18.23 | 29.24                             | 18.72 | 26.82                         |
|         | LLM4CBI <sub>selnov</sub> | 8             | 37.50  | 22            | 18.18  | 35             | 17.14                                | 38             | 31.58                                | 19.38 | 33.44                             | 19.62 | 30.17                         |
|         | LLM4CBI                   | 11            | -  | 26            | -  | 41             | -                                    | 50             | -                                    | 12.90 | -                                 | 13.70 | -                             |
|         | LLM4CBI <sub>ep</sub>     | 8             | 25.00  | 20            | 20.00  | 31             | 6.45                                 | 43             | 11.63                                | 18.98 | 27.66                             | 19.31 | 28.02                         |
|         | LLM4CBI <sub>sp</sub>     | 7             | 42.86  | 23            | 4.35   | 32             | 3.13                                 | 39             | 23.08                                | 17.75 | 22.65                             | 17.87 | 22.22                         |
| LLVM    | LLM4CBI <sub>rand</sub>   | 8             | 25.00  | 23            | 4.35   | 30             | 10.00                                | 41             | 17.07                                | 16.28 | 15.66                             | 16.40 | 15.24                         |
|         | LLM4CBI <sub>selnov</sub> | 8             | 25.00  | 20            | 20.00  | 32             | 3.13                                 | 45             | 6.67                                 | 14.85 | 7.54                              | 14.88 | 6.59                          |
|         | LLM4CBI                   | 10            | -  | 24            | -  | 33             | -                                    | 48             | -                                    | 13.73 | -                                 | 13.90 | -                             |
| ALL     | LLM4CBIep                 | 13            | 61.54  | 44            | 13.64  | 67             | 10.45                                | 85             | 15.29                                | 19.93 | 31.17                             | 20.40 | 32.34                         |
|         | LLM4CBI <sub>sp</sub>     | 12            | 75.00  | 46            | 8.70   | 65             | 13.85                                | 78             | 25.64                                | 19.13 | 30.38                             | 21.15 | 34.74                         |
|         | LLM4CBI <sub>rand</sub>   | 14            | 50.00  | 49            | 2.04   | 67             | 10.45                                | 83             | 18.07                                | 17.26 | 22.83                             | 17.56 | 21.41                         |
|         | LLM4CBIselnov             | 16            | 31.25  | 42            | 19.05  | 70             | 5.71                                 | 83             | 18.07                                | 17.12 | 22.20                             | 17.25 | 20.00                         |
|         | LLM4CBI                   | 21            | -  | 50            | -  | 74             | -                                    | 98             | -                                    | 13.32 | -                                 | 13.80 | -                             |

Note: Columns "↑ \*" present the improvement rates (%) of LLM4CBI over the compared variant approaches in terms of various metrics.

4

5

6

8

9

10

11

12

13

14

ł

int a, b, c, d; char e;

int main () {

d = 0;

foo ();

}

**void** foo () { a = 0; }

unsigned char f;

for (; b < 1; b++)

if (a) { break; }

 $f = 179 * e^{-1}$ 

for  $(e = 1; e \ge 0; e - -)$ 

**c** = **f** << (-1); // **c** = **f** << 1;

uses a simple prompt without data flow and control flow analysis) and LLM4CBI $_{sp}$  (i.e., the approach utilizes specific prompt by giving the "the most complex data and control flow") in terms of all the metrics over all the 120 bugs in GCC and LLVM. Notably, LLM4CBI is able to isolate more 61.54% and 13.64% bugs within the Top-1 and Top-5 files and also improves 31.17% and 32.34% than  $LLM4CBI_{ep}$  in terms of MFR and MAR. Compared with both LLM4CBI<sub>ep</sub> and LLM4CBI<sub>sp</sub>, LLM4CBI shows better results on Top-N metrics. In addition, LLM4CBI also holds a smaller value of MFR and MAR, indicating LLM4CBI has a better compiler bug isolation capability.

The above results indicate that the program complexity metrics are helpful for producing precise prompts, and removing data flow and control flow analysis or replacing it with explicit descriptions to LLMs are not effective. This is reasonable, as LLMs have shown to be limited at semantic understanding [51]. Therefore, with limited prompt description, LLMs may randomly select interesting variables and locations when mutating the failing test program, making it difficult to flip the execution from failing to passing for generating effective test programs for compiler bug isolation.

Contribution of Prompt Selection. We run LLM4CBIrand (i.e., an approach randomly selects a prompt) and LLM4CBI to investigate the contribution of memorized prompt selection component. Table 4 presents the overall results. The results indicate that LLM4CBI outperforms LLM4CBI<sub>rand</sub> as well. Specifically, LLM4CBI demonstrates better performance compared to LLM4CBI<sub>rand</sub>, with substantial improvements of 50.00%, 2.04%, 10.45%, 18.07%, 22.83%, and 21.41% across Top-1, Top-5, Top-10, Top-20, MFR, and MAR metrics, respectively. These results underscore the superiority of our memorized prompt selection based on reinforcement learning over the random strategy.

Contribution of Test Program Validation. Compared with the approaches shown in rows 4 and 5 in Table 4, LLM4CBI outperforms LLM4CBI<sub>selnov</sub> (a variant approach removes the test validation component) for all the metrics for both GCC and LLVM. For the overall benchmarks, LLM4CBI could isolate 31.25% and 19.05% more bugs with Top-1

\*c = 1 % (unsigned int) \*c | 5; 15 15 } } 16 printf ("%d\n", c); 16 printf ("%d\n", b); 17 return 0; 17 return 0; 18 } 18 } (a) LLVM Bug #18000: (invalid (b) GCC Bug #64682 : invalid

1 int a;

3

5 int i:

6

8

10

11

12

14

4 int main (){

for (;

**int** \*c = &b;

{;}

if (\*c)

{

{

**short int b** = 1; // **int b** = 1;

for (i = 0; i < 56; i++)

a: a--)

shift value in Line 12 caused memory access in Line 11 by the mutation in the same line) caused by the mutation in Line 2

Fig. 6. Side effects of the test programs with undefined behaviors (the commented code in green is the original code in the failing test program, and the code with the red box contains undefined behavior)

and Top-5 files than LLM4CBI<sub>selnov</sub>, respectively. In terms of MFR and MAR, LLM4CBI also exhibited significant improvements of 22.20% and 20.00% over LLM4CBIselnov. These results provide compelling evidence that incorporating the test program validation component enhances the effectiveness of compiler bug isolation, thereby confirming its valuable contribution in LLM4CBI.

To further understand why filtering the semantically invalid test programs is important, we showcase two examples with undefined behaviors in Fig. 6 and indicate their side effects for compiler bug isolation. The first example shown in Fig. 6(a) includes an undefined behavior shift, which is generated by the mutation rule replacing a constant value (from "1" to "-1") in Line 12. RecBi ranked this bug at 23<sup>th</sup> due to the interference of the undefined behavior. The second example exposes an undefined behavior memem\_access, which is produced by the mutation rule inserting a modifier of a variable (from int to short int) in Line 2. Because the size of short int (2 bytes in 64-bit system) is shorter than int (4 bytes in 64-bit system), there

TABLE 5 Evaluated open-source LLMs in LLM4CBI

| Models       | Size | Release-Date | Popularity(GitHub) |
|--------------|------|--------------|--------------------|
| Alpaca [27]  | 7B   | March 2023   | 25.0K star         |
| Vicuna [28]  | 7B   | March 2023   | 22.8K star         |
| GPT4ALL [29] | 13B  | March 2023   | 46K star           |

is an out-of-bound read from the variable b, which makes RecBi rank this bug at  $28^{th}$ . Benefiting from the test program validation process, LLM4CBI filter those examples before ranking the suspicious files and finally rank the LLVM bug and GCC bug at  $9^{th}$  and  $5^{th}$ , respectively. This is reasonable, as demonstrated in previous studies [2], [46], [52], modern compilers can have unexpected consequences if the program is semantically invalid. In summary, the semantically invalid test programs can have side effects on the effectiveness of compiler bug isolation, and filtering them could help LLM4CBI improve the ranking results.

**Summary for RQ2.** All three components, including precise prompt production, memorized prompt selection, and lightweight test program validation, contribute to the effectiveness of LLM4CBI.

## 4.5 Answers to RQ3

### 4.5.1 Experimental Settings

Table 5 presents the evaluated LLMs in this study, with column **Sizes** reflecting the model sizes in billions of parameters, **Release-Date** showing when the LLM is released, and **Popularity** indicating the number of GitHub stars or users counted by 1st June 2023. We evaluate three of the most representative and popular LLMs. We choose the above LLMs mainly because (1) they are very popular that the number of stars soared to 20k+ in a few months and (2) they are proven to be effective in code generation tasks [12], [26], [27], [29]. Based on the selected LLMs, we design three new variant approaches, i.e., LLM4CBI(Alpaca), LLM4CBI(Vicuna), and LLM4CBI(GPT4ALL), by replacing the LLMs in LLM4CBI to answer this RQ.

Setting Up Different LLMs. For the three LLMs, we download the GGML<sup>2</sup> format of these models from HuggingFace website<sup>3</sup> and use the python binding llama-cpp-python<sup>4</sup> of llama.cpp<sup>5</sup> to run these models in the machine that only supports CPU. Specifically, we use a web server supported by llama-cpp-python, which aims to act as a drop-in replacement for the OpenAI API. This feature allows us to use llama.cpp compatible models with any OpenAIcompatible client (language libraries, services, etc.). Note that it would be easy and invoke little human effort to support any other interesting models in LLM4CBI. The only thing users need to do is to provide the GGML format model, either directly download from the HuggingFace website or product using the detailed and actively maintained tutorials in GGML's homepage<sup>2</sup>, for llama-cpp-python web server.

TABLE 6 Compiler bug isolation capability of different LLMs in LLM4CBI

| Subject | Approach         | Top-1 | Top-5 | Top-10 | Top-20 |
|---------|------------------|-------|-------|--------|--------|
|         | LLM4CBI(Alpaca)  | 1     | 10    | 16     | 22     |
| CCC     | LLM4CBI(Vicuna)  | 5     | 15    | 19     | 27     |
| GCC     | LLM4CBI(GPT4ALL) | 2     | 7     | 15     | 21     |
|         | LLM4Cbi          | 11    | 26    | 41     | 50     |
|         | LLM4CBI(Alpaca)  | 1     | 9     | 18     | 23     |
| TIVM    | LLM4CBI(Vicuna)  | 1     | 9     | 19     | 32     |
|         | LLM4CBI(GPT4ALL) | 1     | 5     | 18     | 26     |
|         | LLM4Cbi          | 10    | 24    | 33     | 48     |
|         | LLM4CBI(Alpaca)  | 2     | 19    | 34     | 45     |
| A T T   | LLM4CBI(Vicuna)  | 6     | 24    | 38     | 59     |
| ALL     | LLM4CBI(GPT4ALL) | 3     | 12    | 33     | 47     |
|         | LLM4CBI          | 21    | 48    | 74     | 98     |

Note: LLM4CBI uses GPT-3.5 as the default LLM.

**Comparison Strategies**. We run those variants within one hour limit and then compare the Top-N metrics for each approach. We do not repeatedly run those models mainly because we aim to demonstrate the extendability of replacing different LLMs in LLM4CBI.

### 4.5.2 Experimental Results

Table 6 shows that all the designed variant approaches, i.e., LLM4CBI(Alpaca), LLM4CBI(Vicuna), and LLM4CBI(GPT4ALL), contribute to the compiler bug isolation task. The results indicate that different LLMs can have different capabilities for generating test programs for compiler bug isolation, and GPT-3.5 (used as the default model in LLM4CBI) achieves the best performance compared with other LLMs. Serval reasons made the performance of other LLMs not as good as GPT-3.5 used in LLM4CBI:

- Only give suggestion responses. Many outputs from those models are suggestions telling users how to change the code rather than the actual code. For example, on isolating LLVM #17388 with the prompt "replacing a binary operator with another valid one on the variables in the list ['a', 'c']", LLM4CBI(Alpaca) responses, "You can replace the binary operator '||' with the logical operator '&&'''. Such output did not directly contain the complete test programs, but that information is still useful for helping users manually write a good passing test program.
- Limited code generation capabilities. Although other LLMs are targeting a comparable performance compared with GPT-3.5 or GPT-4, they may still be limited by the scale of training data. For example, The model Alpaca used text-davinci-003 model to generate 52K instruction data as training data, which may still be limited compared with the training data scale of GPT-3.5 (although OpenAI did not disclose the actual number).
- Performance issue. Running LLMs typically requires a powerful GPU to get better performance. Since our experiments run only in CPUs without GPUs, the response time for other LLMs is larger. Based on our observation, the response time of getting an answer from those LLMs takes appropriately 300 seconds, which significantly reduces the effectiveness of those approaches. In contrast, GPT-3.5 only invokes API for the code generation, and

<sup>2.</sup> https://github.com/ggerganov/ggml

<sup>3.</sup> https://huggingface.co/

<sup>4.</sup> https://github.com/abetlen/llama-cpp-python

<sup>5.</sup> The goal of llama.cpp is to run LLMs using 4-bit integer quantization on a MacBook only with CPU.

the response time is less than 10 seconds, which makes LLM4CBI have a better capability.

Although the results from other LLMs are not as good as GPT-3.5, we show the ease in adopting new LLMs in LLM4CBI. With the rapid development of more powerful LLMs, such as Falcon [53], [54], we believe advanced techniques can mitigate the above limitations and further assist the compiler bug isolation task in the near future.

**Summary for RQ3.** LLM4CBI is extensible, allowing for easy integration with other LLMs.

# 5 DISCUSSION

In this section, we first discuss the comparison results with GPT-4 and then evaluate the impact of different *temperature* values used in LLM4CBI. Finally, we discuss some limitations of LLM4CBI.

#### 5.1 Comparison with GPT-4

In this study, we are unable to conduct large-scale experiments using GPT-4 in LLM4CBI due to its higher API cost<sup>6</sup> compared to GPT-3.5. However, we did run two cases using a variant of LLM4CBI, called LLM4CBI(GPT-4), which incorporates GPT-4. Interestingly, the results demonstrated that LLM4CBI(GPT-4) outperformed LLM4CBI, with both Top 20+ bugs being ranked in the Top-5. The improved performance of LLM4CBI(GPT-4) can be attributed to two main factors. First, GPT-4 generated a smaller number of test programs with syntax errors, indicating a higher quality of output. Second, GPT-4 exhibits a better understanding of the prompt, leading to improved results [12], [28]. As LLMs continue to advance rapidly, we anticipate the availability of more capable and user-friendly models that can be integrated into LLM4CBI, further enhancing the compiler bug isolation capabilities of LLM4CBI.

## 5.2 Different temperature Settings in LLMs

The temperature parameter in LLMs, such as GPT-3.5, plays a crucial role in controlling the randomness of the generated output. A lower temperature value makes the output more deterministic, while a higher temperature value increases randomness. In the context of LLM4CBI, it is important to investigate the impact of different temperature values on the performance of test program generation for compiler bug isolation. To this end, we conducted experiments using temperature values of 0.4, 0.6, 0.8, 1.0, and 1.2. The bug isolation capabilities of LLM4CBI were compared under these different temperature settings, and the results are shown in Fig. 7. The results show that the default temperature value of 1.0 performs the best for LLM4CBI. This finding aligns with expectations since OpenAI has fine-tuned this parameter and set it as the default value, indicating that it yields optimal results.



Fig. 7. The results of the impact of different temperature settings

## 5.3 Limitations of LLM4CBI

The limitations in LLM4CBI inherit the issues from SBFL techniques and LLMs. First, SBFL suffers from tie issues [55], [56]. A possible solution is to address this issue by incorporating the use of commit history information [57]. Second, LLMs may generate syntax invalid programs, which may reduce the effectiveness of LLM4CBI. However, based on the experimental results, the number of invalid test programs is acceptable and does not affect the results much. A more effective approach could leverage the program repair technique [19] to repair the code generated by LLMs automatically. We leave further investigation on the above two directions as our future work.

# 6 THREATS TO VALIDITY

This section discusses the *internal*, *external*, and *construct* threats of LLM4CBI.

The *internal* validity concerns stem from the implementation of LLM4CBI and comparative approaches (DiWi [3] and RecBi [4]). To mitigate this threat, we have adopted the implementation provided by the previous studies [3], [4]. As for LLM4CBI, we have meticulously developed its implementation by leveraging well-established libraries, as expounded upon in Section 4.1, and have conducted thorough code checking of the code. For the tool used in test program validation, Frama-C [40] can not detect all the undefined behaviors in the programs as the identification of undefined behavior in the programs is typically a challenging problem [58], [59]. We plan to leverage more advanced techniques to detect potential undefined behaviors in the test programs.

The *external* validity of our study can be influenced by two key factors: the selection of compilers and the presence of bugs. To ensure the reliability of our findings, we have followed the established practices in prior research on compiler bug isolation [3], [4] when selecting compilers. Following these approaches, we have employed two widely used open-source C compilers, GCC and LLVM, which are renowned for their popularity and extensive usage within the community. Regarding the bugs used in our study, we chose a comprehensive set of 120 real compiler bugs, encompassing all known bugs from prior investigations in the field of compiler bug isolation. To further bolster the external validity of our research and address potential threats, we are committed to expanding our bug dataset by incorporating additional real compiler bugs.

<sup>6.</sup> https://openai.com/pricing

The *construct* validity threats are subject to potential threats related to randomness, evaluation metrics, and parameter settings during the evaluation process. We address these concerns by (1) repeating experiments three times and calculating median results to account for randomness, thereby reducing the impact of random variations; (2) employing widely-used bug localization metrics to assess the effectiveness of LLM4CBI to ensure the reliability and comparability of our evaluation results; (3) providing explicit parameter configurations and thoroughly investigating their impact in Section 5. By doing so, we enhance transparency and enable a deeper understanding of the influence of different parameter settings.

## 7 RELATED WORK

This section surveys the most related works in this study, namely compiler debugging and LLMs for code generation.

Compiler Debugging. Our study is primarily related to two recent works: DiWi [3] and RecBi [4]. Both are general solutions for isolating all kinds of bugs in compilers. These works address the problem of isolating compiler bugs by transforming them into the generation of passing test programs. DiWi and RecBi achieve this by first utilizing mutation operators (DiWi focuses on local mutation operators while RecBi supports structural mutation operators) to generate a set of passing test programs similar to the failing test program, but without triggering the bug. Then, they employ spectrum-based bug localization techniques [7], [57] to rank the buggy compiler files by comparing execution traces between the generated passing test programs and the failing test program. LocSeq [41] focuses on isolating optimization bugs only in LLVM, while ODFL [42] aims to isolate bugs only in GCC. We did not compare LLM4CBI with either LocSeq or ODFL mainly because they are not general enough and can only be applicable to specific middleend compiler optimization bugs. In contrast, LLM4CBI is capable of isolating all kinds of bugs in compilers, including syntax analyzer, semantic analyzer, and back-end bugs.

In addition, Zeller [60] introduces a method to facilitate GCC debugging by calculating the cause-effect chain through a comparison of program states between a passing run and a failing run. Holmes and Groce [61], [62] propose a method to localize compiler bugs by comparing a set of compiler mutants. Regarding compiler debugging techniques for other programming languages, Ogata et al. [63] present an approach for debugging the just-in-time compiler in a Java virtual machine. HeuiChan et al. [64], [65] leverage dynamic analysis to locate bugs in JIT compilers.

Different from those works, we follow the existing strategy to generate a set of effective test programs for compiler bug isolation. In contrast, we propose a new structural mutation strategy to mutate failing test programs effectively: we support complete control-flow statements mutation that includes both statement conditions and bodies. Besides, LLM4CBI only involves little human effort to accomplish the test program mutation process.

**LLMs for Code Generation.** The emergence of LLMs has sparked significant interest in their application to code generation tasks. Ling et al. [66] follow an *encoder-decoder* design and use a sequence-to-sequence LSTM model with

attention and a copy mechanism to generate Java and Python codes. Iyer et al. [67] use a grammar-aware decoder to generate syntactically valid Java parse trees followed by Java codes using a two-step attention mechanism. Code-BERT [68] and GraphCodeBERT [69] inherit the design of BERT [70] which are *encoder*-only models to generate codes. Moreover, CodeT5 [71] and PLBART [72] leverages encoderdecoder architecture for generating codes. GLAsT [73] and VGen [74] apply *decoder*-only LLMs for generating Verilog RTL Code. Other recent LLMs, such as ChatGPT [5], Vicuna [28], WizardLM [75], and StableLM [76], all follow *decoder*only architecture to generate various codes in Python, Java, C/C++, and SQL.

In this study, we opt for the *decoder*-only models that follow the prompt-response dialog paradigm to generate the whole test program for compiler bug isolation tasks. Different from existing approaches, we design a new pattern for precisely producing prompts in LLM4CBI. The program's data and control flow complexity are measured to fill in the designed pattern. Furthermore, a memorized selection and a test program validation strategy are proposed to select the proper prompt for effectively taming LLMs for test program mutation. We also demonstrate LLM4CBI can be extensible for adopting different LLMs for compiler bug isolation.

# 8 CONCLUSION AND FUTURE WORK

This paper presents LLM4CBI, a new approach to tame LLMs for generating effective test programs for compiler bug isolation. In LLM4CBI, three new components, i.e., precise prompt production, memorized prompt selection, and lightweight test program validation, are designed to tackle the two main challenges of formulating precise prompts and selecting specialized prompts. Empirical evaluation using 120 real-world bugs from GCC and LLVM demonstrates the effectiveness of LLM4CBI over state-of-the-art approaches. Notably, LLM4CBI achieves significant improvements ranging from 13.6% to 90.9% in various settings than DiWi and RecBi, respectively. Furthermore, we demonstrate that LLM4CBI is extensible, highlighting its ease of extension to other LLMs for the compiler bug isolation task.

**Future Work**. In addition to the promising results presented in this paper, there are several exciting directions for further enhancing the capabilities of LLM4CBI. We are actively exploring the following directions:

- Interactive bug isolation. Taking inspiration from interactive fault localization techniques that leverage user feedback [77], we may incorporate interactive elements into LLM4CBI. In detail, by treating LLMs (e.g., ChatGPT) as a user, we can enable them to learn continuously from the feedback received during the bug isolation process, thereby improving the isolation capability.
- Intelligent bug isolation. To empower LLMs with more detailed information, such as coverage data, we can enable them to make intelligent decisions regarding potentially buggy files. Specifically, we plan to guide LLMs to employ different evaluation strategies (e.g., different formulas used in SBFL) and fine-tune the parameters of LLMs to facilitate compiler bug isolation.

## REFERENCES

- [1] J. Chen, J. Patra, M. Pradel, Y. Xiong, H. Zhang, D. Hao, and L. Zhang, "A survey of compiler testing," ACM Computing Surveys (CSUR), vol. 53, no. 1, pp. 1-36, 2020.
- X. Yang, Y. Chen, E. Eide, and J. Regehr, "Finding and understanding bugs in c compilers," in Proceedings of the 32nd ACM SIGPLAN conference on Programming Language Design and Implementation (PLDI), 2011, pp. 283-294.
- [3] J. Chen, J. Han, P. Sun, L. Zhang, D. Hao, and L. Zhang, "Compiler bug isolation via effective witness test program generation," in Proceedings of the 27th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering (ESEC/FSE), 2019, pp. 223–234.
- [4] J. Chen, H. Ma, and L. Zhang, "Enhanced compiler bug isolation via memoized search," in Proceedings of the 35th IEEE/ACM International Conference on Automated Software Engineering (ASE), 2020, pp. 78-89.
- OpenAI. (2022) ChatGPT: Optimizing language models for [5] dialogue. [Online]. Available: https://openai.com/blog/chatgpt/
- Z. Liu, C. Chen, J. Wang, X. Che, Y. Huang, J. Hu, and Q. Wang, [6] "Fill in the blank: Context-aware automated text input generation for mobile gui testing," arXiv preprint arXiv:2212.04732, 2022.
- R. Abreu, P. Zoeteweij, and A. J. Van Gemund, "On the accu-[7] racy of spectrum-based fault localization," in Testing: Academic and industrial conference practice and research techniques-MUTATION (TAICPART-MUTATION), 2007, pp. 89-98
- W. E. Wong, R. Gao, Y. Li, R. Abreu, and F. Wotawa, "A survey [8] on software fault localization," IEEE Transactions on Software Engineering, vol. 42, no. 8, pp. 707-740, 2016.
- I. Sutskever, O. Vinyals, and Q. V. Le, "Sequence to sequence learning with neural networks," *Advances in neural information* [9] processing systems, vol. 27, 2014. [10] Y. Liu, "Fine-tune bert for extractive summarization," arXiv
- preprint arXiv:1903.10318, 2019.
- [11] Z. Yang, Z. Dai, Y. Yang, J. Carbonell, R. R. Salakhutdinov, and Q. V. Le, "Xlnet: Generalized autoregressive pretraining for language understanding," Advances in neural information processing systems, vol. 32, 2019.
- [12] J. Liu, C. S. Xia, Y. Wang, and L. Zhang, "Is Your Code Generated by ChatGPT Really Correct? Rigorous Evaluation of Large Language Models for Code Generation," arXiv preprint arXiv:2305.01210, 2023.
- [13] P. Liu, W. Yuan, J. Fu, Z. Jiang, H. Hayashi, and G. Neubig, "Pre-train, prompt, and predict: A systematic survey of prompting methods in natural language processing," ACM Comput. Surv., vol. 55, no. 9, pp. 195:1–195:35, 2023. [Online]. Available: https://doi.org/10.1145/3560815
- [14] J. White, Q. Fu, S. Hays, M. Sandborn, C. Olea, H. Gilbert, A. Elnashar, J. Spencer-Smith, and D. C. Schmidt, "A prompt pattern catalog to enhance prompt engineering with ChatGpt," arXiv preprint arXiv:2302.11382, 2023.
- [15] L. Reynolds and K. McDonell, "Prompt programming for large language models: Beyond the few-shot paradigm," in Extended Abstracts of the 2021 CHI Conference on Human Factors in Computing Systems, 2021, pp. 1–7.
- [16] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell et al., "Language models are few-shot learners," Advances in neural information processing systems, vol. 33, pp. 1877-1901, 2020.
- [17] C. Niu, C. Li, V. Ng, D. Chen, J. Ge, and B. Luo, "An empirical comparison of pre-trained models of source code," arXiv preprint arXiv:2302.04026, 2023.
- [18] C. S. Xia, Y. Wei, and L. Zhang, "Automated program repair in the era of large pre-trained language models," in Proceedings of the ACM/IEEE 45th International Conference on Software Engineering (ICSE), 2023, pp. 1-12.
- [19] Z. Fan, X. Gao, A. Roychoudhury, and S. H. Tan, "Automated repair of programs from large language models," arXiv preprint arXiv:2205.10583, 2022
- [20] Y. Deng, C. S. Xia, H. Peng, C. Yang, and L. Zhang, "Fuzzing deep-learning libraries via large language models," arXiv preprint arXiv:2212.14834, 2022.
- [21] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin, "Attention is all you need," in Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA, 2017, pp. 5998-6008.

[Online]. Available: https://proceedings.neurips.cc/paper/2017/ hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html

- [22] F. Cassano, J. Gouwar, D. Nguyen, S. Nguyen, L. Phipps-Costin, D. Pinckney, M.-H. Yee, Y. Zi, C. J. Anderson, M. Q. Feldman et al., "Multipl-e: a scalable and polyglot approach to benchmarking neural code generation," IEEE Transactions on Software Engineering, pp. 1-17, 2023.
- [23] E. Nijkamp, B. Pang, H. Hayashi, L. Tu, H. Wang, Y. Zhou, S. Savarese, and C. Xiong, "Codegen: An open large language model for code with multi-turn program synthesis," Proceedings of the 11th International Conference on Learning Representations (ICLR), 2023.
- D. Fried, A. Aghajanyan, J. Lin, S. Wang, E. Wallace, F. Shi, R. Zhong, W.-t. Yih, L. Zettlemoyer, and M. Lewis, "Incoder: A [24] generative model for code infilling and synthesis," Proceedings of the 7th International Conference on Learning Representations (ICLR), pp. 1-26, 2022.
- [25] F. F. Xu, U. Alon, G. Neubig, and V. J. Hellendoorn, "A systematic evaluation of large language models of code," in Proceedings of the 6th ACM SIGPLAN International Symposium on Machine Programming (ISMP), 2022, pp. 1-10.
- [26] H. Touvron, T. Lavril, G. Izacard, X. Martinet, M.-A. Lachaux, T. Lacroix, B. Rozière, N. Goyal, E. Hambro, F. Azhar, A. Rodriguez, A. Joulin, E. Grave, and G. Lample, "LLaMA: Open and efficient foundation language models," arXiv preprint arXiv:2302.13971, 2023.
- [27] R. Taori, I. Gulrajani, T. Zhang, Y. Dubois, X. Li, C. Guestrin, P. Liang, and T. B. Hashimoto, "Stanford alpaca: An instructionfollowing llama model," https://github.com/tatsu-lab/stanford\_ alpaca, 2023.
- [28] W.-L. Chiang, Z. Li, Z. Lin, Y. Sheng, Z. Wu, H. Zhang, L. Zheng, S. Zhuang, Y. Zhuang, J. E. Gonzalez *et al.*, "Vicuna: An opensource chatbot impressing gpt-4 with 90%\* ChatGpt quality," 2023.
- [29] Y. Anand, Z. Nussbaum, B. Duderstadt, B. Schmidt, and A. Mulyar, "GPT4All: Training an assistant-style chatbot with large scale data distillation from gpt-3.5-turbo," https://github.com/ nomic-ai/gpt4all, 2023.
- [30] T. J. McCabe, "A complexity measure," IEEE Transactions on Software Engineering, no. 4, pp. 308-320, 1976.
- [31] C. D. Newman, T. Sage, M. L. Collard, H. W. Alomari, and J. I. Maletic, "srcslice: A tool for efficient static forward slicing," in Proceedings of the 38th International Conference on Software Engineering Companion (SEC), 2016, pp. 621-624.
- [32] A. V. Aho, M. S. Lam, R. Sethi, and J. D. Ullman, Compilers: Principles, Techniques, and Tools (2nd Edition). Addison-Wesley Longman Publishing Co., Inc., 2006.
- [33] L. P. Kaelbling, M. L. Littman, and A. W. Moore, "Reinforcement learning: A survey," Journal of artificial intelligence research, vol. 4, pp. 237–285, 1996.
- [34] R. S. Sutton and A. G. Barto, Reinforcement learning: An introduction. MIT Press, 2018.
- [35] V. Mnih, K. Kavukcuoglu, D. Silver, A. Graves, I. Antonoglou, D. Wierstra, and M. Riedmiller, "Playing atari with deep reinforcement learning," arXiv preprint arXiv:1312.5602, 2013.
- [36] R. S. Sutton, D. McAllester, S. Singh, and Y. Mansour, "Policy gradient methods for reinforcement learning with function approximation," Advances in neural information processing systems, vol. 12, 1999.
- [37] V. Konda and J. Tsitsiklis, "Actor-critic algorithms," Advances in neural information processing systems, vol. 12, 1999.
- [38] V. Mnih, A. P. Badia, M. Mirza, A. Graves, T. Lillicrap, T. Harley, D. Silver, and K. Kavukcuoglu, "Asynchronous methods for deep reinforcement learning," in Proceedings of the International Conference On Machine Learning (ICML), 2016, pp. 1928-1937.
- I. Grondman, L. Busoniu, G. A. Lopes, and R. Babuska, "A survey [39] of actor-critic reinforcement learning: Standard and natural policy gradients," IEEE Transactions on Systems, Man, and Cybernetics, vol. 42, no. 6, pp. 1291-1307, 2012.
- [40] F. Kirchner, N. Kosmatov, V. Prevosto, J. Signoles, and B. Yakobowski, "Frama-c: A software analysis perspective," Formal aspects of computing, vol. 27, no. 3, pp. 573-609, 2015.
- Z. Zhou, H. Jiang, Z. Ren, Y. Chen, and L. Qiao, "Locseq: Automated localization for compiler optimization sequence bugs of llvm," IEEE Transactions on Reliability, vol. 71, no. 2, pp. 896-910, 2022
- [42] J. Yang, Y. Yang, M. Sun, M. Wen, Y. Zhou, and H. Jin, "Isolating compiler optimization faults via differentiating finer-grained

options," in IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER), 2022, pp. 481–491.

- [43] R. Laboratories. (2023) Oclint. [Online]. Available: https: //github.com/oclint
- [44] GNU. (2023) Gcov. [Online]. Available: https://gcc.gnu.org/ onlinedocs/gcc/Gcov.html
- [45] P. Foundation. (2023) Pytorch. [Online]. Available: https: //pytorch.org
- [46] H. Tu, H. Jiang, Z. Zhou, Y. Tang, Z. Ren, L. Qiao, and L. Jiang, "Detecting C++ compiler front-end bugs via grammar mutation and differential testing," *IEEE Transactions on Reliability*, pp. 1–15, 2022.
- [47] H. Jiang, Z. Zhou, Z. Ren, J. Zhang, and X. Li, "CTOS: Compiler testing for optimization sequences of llvm," *IEEE Transactions on Software Engineering*, vol. 48, no. 7, pp. 2339–2358, 2021.
  [48] H. Tu, H. Jiang, X. Li, Z. Ren, Z. Zhou, and L. Jiang, "RemGen:
- [48] H. Tu, H. Jiang, X. Li, Z. Ren, Z. Zhou, and L. Jiang, "RemGen: Remanufacturing a random program generator for compiler testing," in *IEEE 33rd International Symposium on Software Reliability Engineering (ISSRE)*, 2022, pp. 529–540.
- [49] D. Jeffrey, N. Gupta, and R. Gupta, "Fault localization using value replacement," in *Proceedings of the 2008 ACM SIGSOFT International Symposium on Software Testing and Analysis (ISSTA)*, 2008, pp. 167–178.
- [50] S. Pearson, J. Campos, R. Just, G. Fraser, R. Abreu, M. D. Ernst, D. Pang, and B. Keller, "Evaluating and improving fault localization," in *Proceedings of the 39th IEEE/ACM International Conference* on Software Engineering (ICSE), 2017, pp. 609–620.
- [51] W. Ma, S. Liu, W. Wang, Q. Hu, Y. Liu, C. Zhang, L. Nie, and Y. Liu, "The scope of ChatGPT in software engineering: A thorough investigation," arXiv preprint arXiv:2305.12138, 2023.
- [52] C. Sun, V. Le, Q. Zhang, and Z. Su, "Toward understanding compiler bugs in gcc and llvm," in *Proceedings of the 25th ACM* SIGSOFT International Symposium on Software Testing and Analysis (ISSTA), 2016, pp. 294—305.
- [53] E. Almazrouei, A. Cappelli, R. Cojocaru, M. Debbah, E. Goffinet, D. Heslow, J. Launay, Q. Malartic, B. Noune, B. Pannier, and G. Penedo, "Falcon-40b: an open large language model with stateof-the-art performance," *Hugging Face*, 2023.
- [54] G. Penedo, Q. Malartic, D. Hesslow, R. Cojocaru, A. Cappelli, H. Alobeidli, B. Pannier, E. Almazrouei, and J. Launay, "The refinedweb dataset for falcon llm: outperforming curated corpora with web data, and web data only," *arXiv preprint arXiv:2306.01116*, 2023.
- [55] Y. Yu, J. A. Jones, and M. J. Harrold, "An empirical study of the effects of test-suite reduction on fault localization," in *Proceedings* of the 30th International Conference on Software Engineering (ICSE), 2008, pp. 201–210.
- [56] X. Xu, V. Debroy, W. Eric Wong, and D. Guo, "Ties within fault localization rankings: Exposing and addressing the problem," *International Journal of Software Engineering and Knowledge Engineering*, vol. 21, no. 06, pp. 803–827, 2011.
- [57] M. Wen, J. Chen, Y. Tian, R. Wu, D. Hao, S. Han, and S.-C. Cheung, "Historical spectrum based fault localization," *IEEE Transactions on Software Engineering*, vol. 47, no. 11, pp. 2348–2368, 2019.
- [58] J. Lee, Y. Kim, Y. Song, C.-K. Hur, S. Das, D. Majnemer, J. Regehr, and N. P. Lopes, "Taming undefined behavior in llvm," ACM SIGPLAN Notices, vol. 52, no. 6, pp. 633–647, 2017.
- [59] X. Wang, N. Zeldovich, M. F. Kaashoek, and A. Solar-Lezama, "Towards optimization-safe systems: Analyzing the impact of undefined behavior," in *Proceedings of the Twenty-Fourth ACM Symposium on Operating Systems Principles (SOSP)*, 2013, pp. 260– 275.
- [60] A. Zeller, "Isolating cause-effect chains from computer programs," ACM SIGSOFT Software Engineering Notes, vol. 27, no. 6, pp. 1–10, 2002.

- [61] J. Holmes and A. Groce, "Causal distance-metric-based assistance for debugging after compiler fuzzing," in *IEEE 29th International Symposium on Software Reliability Engineering (ISSRE)*, 2018, pp. 166–177.
- [62] H. Josie and G. Alex, "Using mutants to help developers distinguish and debug (compiler) faults," *Software Testing, Verification* and Reliability, vol. 30, no. 2, p. e1727, 2020.
- [63] B.-Y. E. Chang, A. Chlipala, G. C. Necula, and R. R. Schneck, "Type-based verification of sssembly language for compiler debugging," in *Proceedings of the ACM International Workshop on Types* in Languages Design and Implementation, 2005, pp. 91–102.
- [64] H. Lim and S. Debray, "Automatically localizing dynamic code generation bugs in jit compiler back-end," in *Proceedings of the 32nd* ACM SIGPLAN International Conference on Compiler Construction (CC), 2023, pp. 145–155.
- [65] H. Lim and S. K. Debray, "Automated bug localization in jit compilers," Proceedings of the 17th ACM SIGPLAN/SIGOPS International Conference on Virtual Execution Environments, 2021.
- [66] W. Ling, P. Blunsom, E. Grefenstette, K. M. Hermann, T. Kočiský, F. Wang, and A. Senior, "Latent predictor networks for code generation," in *Proceedings of the 54th Annual Meeting of the Association* for Computational Linguistics (Long Papers), 2016, pp. 599–609.
- [67] S. Iyer, I. Konstas, A. Cheung, and L. Zettlemoyer, "Mapping language to code in programmatic context," in *Proceedings of the* 2018 Conference on Empirical Methods in Natural Language Processing (EMNLP), 2018, pp. 1643–1652.
- [68] Z. Feng, D. Guo, D. Tang, N. Duan, X. Feng, M. Gong, L. Shou, B. Qin, T. Liu, D. Jiang *et al.*, "Codebert: A pre-trained model for programming and natural languages," in *Findings of the Association for Computational Linguistics*, 2020, pp. 1536–1547.
- [69] D. Guo, S. Ren, S. Lu, Z. Feng, D. Tang, S. Liu, L. Zhou, N. Duan, J. Yin, D. Jiang, and M. Zhou, "Graphcodebert: Pre-training code representations with data flow," *Proceedings of the 11th International Conference on Learning Representations (ICLR)*, vol. abs/2009.08366, 2020.
- [70] J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova, "Bert: Pretraining of deep bidirectional transformers for language understanding," arXiv preprint arXiv:1810.04805, 2018.
- [71] Y. Wang, H. Le, A. D. Gotmare, N. D. Bui, J. Li, and S. C. Hoi, "Codet5+: Open code large language models for code understanding and generation," arXiv preprint arXiv:2305.07922, 2023.
- [72] W. U. Ahmad, S. Chakraborty, B. Ray, and K. Chang, "Unified pre-training for program understanding and generation," in *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT*, 2021, pp. 2655–2668.
- [73] C. B. Harris and I. G. Harris, "Glast: Learning formal grammars to translate natural language specifications into hardware assertions," in *Design, Automation & Test in Europe Conference & Exhibition (DATE)*, 2016, pp. 966–971.
- [74] S. Thakur, B. Ahmad, Z. Fan, H. Pearce, B. Tan, R. Karri, B. Dolan-Gavitt, and S. Garg, "Benchmarking large language models for automated verilog rtl code generation," in 2023 Design, Automation & Test in Europe Conference & Exhibition (DATE), 2023, pp. 1–6.
- [75] C. Xu, Q. Sun, K. Zheng, X. Geng, P. Zhao, J. Feng, C. Tao, and D. Jiang, "Wizardlm: Empowering large language models to follow complex instructions," *arXiv e-prints*, pp. 1–39, 2023.
- [76] Stability-AI. (2023) Stablelm: Stability ai language models. [Online]. Available: https://github.com/Stability-AI/StableLM
- [77] L. Gong, D. Lo, L. Jiang, and H. Zhang, "Interactive fault localization leveraging simple user feedback," in *Proceedings of the 28th IEEE International Conference on Software Maintenance (ICSM)*, 2012, pp. 67–76.